


AMC(M)1500S



AA
90°
• AR : 9°~13°
• RR : -14°~5°

(MM)

Обозначение		ØD	ØD2	Ød	Ød1	Ød2	Ød3	a	b	E	F	ap	
AMC(M) 15040HS	5	40	34	16	9	14	-	8.4	5.6	19	40	9	0.22
15050HS	6	50	42	22	11	18	-	10.4	6.3	21	40	9	0.34
15063HS	8	63	49	22	11	18	-	10.4	6.3	21	40	9	0.57
15080HS	10	80	57	25.4(27)	14	25	35	9.5(12.4)	6(7)	24(23)	50	9	1.10
15100HS	12	100	67	31.75(32)	18	26	42	12.7(14.4)	8(8)	32(26)	63	9	2.10

• () Метрическая система

Применяемые СМП

APMT-MM

APMT-MF




Обозначение	Тв. сплав с покрытием								Кермет			Тв. сплав				Стр.		
	NCM325	NCM335	NC5330	PC3500	PC5300	PC3545	PC9530	PC6510	PC215K	PD2000	CN2000	CN20	CN30	H01	G10		ST30A	ST20
APMT 0903PDSR-MM			●	●	●	●												E05
090308PDSR-MM			●	●	●	●												
090312R-MM				●	●	●												
090316R-MM				●	●	●												
090320R-MM				●	●	●												

Применяемые оправки

Обозначение	Ød	Оправка с хвостовиком BT
AMC(M) 15040HS	16	BT □□-FMC16-□□
15050HS	22	BT □□-FMC22-□□
15063HS		
15080HS	25.4	BT □□-FMA25.4-□□
15100HS	27	BT □□-FMC27-□□
	31.75	BT □□-FMA31.75-□□
	32	BT □□-FMC32-□□

Комплектующие



FTKA02565S



TW08S

