


# IFE2000 / 3000 (Цилиндрическая стандартная форма)



ØD	Предельные отклонения D
Ø1.0 ~ Ø8.0	0 ~ -0.020
Ø8.5 ~ Ø11.5	0 ~ -0.025
Ø12.0 ~ Ø20.0	0 ~ -0.030

(MM)

Обозначение	ØD	Ød	l	L
<b>IFE</b>				
<b>2</b> 2010-040	1	6	2.5	40
2015-040	1.5	6	4	40
2020-040	2	6	6	40
2025-040	2.5	6	8	40
2030-045	3	6	8	45
2035-045	3.5	6	10	45
2040-045	4	6	11	45
2045-045	4.5	6	11	45
2050-050	5	6	13	50
2055-050	5.5	6	13	50
2060-050	6	6	13	50
2065-060	6.5	8	16	60
2070-060	7	8	16	60
2075-060	7.5	8	16	60
2080-060	8	8	19	60
2085-070	8.5	10	19	70
2090-070	9	10	19	70
2095-070	9.5	10	19	70
2100-070	10	10	22	70
2105-075	10.5	12	22	75
2110-075	11	12	22	75
2115-075	11.5	12	22	75
2120-075	12	12	26	75
2130-085	13	16	26	85
2140-085-S14	14	14	26	85
2140-085	14	16	26	85
2150-090	15	16	26	90
2160-100	16	16	32	100
2180-100-S18	18	18	32	100
2180-100	18	20	32	100
2200-105	20	20	38	105
<b>IFE</b>				
<b>3</b> 3020-040	2	6	6	40
3030-045	3	6	8	45
3040-045	4	6	11	45
3050-050	5	6	13	50
3060-050	6	6	13	50
3070-060	7	8	16	60
3080-060	8	8	19	60
3090-070	9	10	19	70
3100-070	10	10	22	70
3110-075	11	12	22	75
3120-075	12	12	26	75
3130-085	13	16	26	85
3140-085-S14	14	14	26	85
3140-085	14	16	26	85
3150-090	15	16	26	90
3160-100	16	16	32	100

