


IFE2000-T (Коническая форма)



ØD	Предельные отклонения ℓ
Ø1.0 ~ Ø8.0	0 ~ -0.020
Ø8.5 ~ Ø11.5	0 ~ -0.025
Ø12.0 ~ Ø20.0	0 ~ -0.030

(mm)

Обозначение	ØD	Ød	L	ℓ	θ°
IFE					
2 2030-045-T05	3	6	45	10	0.5°
2030-045-T10	3	6	45	10	1°
2030-045-T15	3	6	45	10	1.5°
2030-045-T20	3	6	45	10	2°
2030-045-T25	3	6	45	10	2.5°
2030-045-T30	3	6	45	10	3°
2040-045-T05	4	6	45	12	0.5°
2040-045-T10	4	6	45	12	1°
2040-045-T15	4	6	45	12	1.5°
2040-045-T20	4	6	45	12	2°
2040-045-T25	4	6	45	12	2.5°
2040-045-T30	4	6	45	12	3°
2050-050-T05	5	6	50	15	0.5°
2050-050-T10	5	6	50	15	1°
2050-050-T15	5	6	50	15	1.5°
2050-050-T20	5	8	50	15	2°
2050-050-T25	5	8	50	15	2.5°
2050-050-T30	5	8	50	15	3°
2060-050-T05	6	8	50	15	0.5°
2060-050-T10	6	8	50	15	1°
2060-050-T15	6	8	50	15	1.5°
2060-050-T20	6	8	50	15	2°
2060-050-T25	6	8	50	15	2.5°
2060-050-T30	6	8	50	15	3°
2080-060-T05	8	10	60	20	0.5°
2080-060-T10	8	10	60	20	1°
2080-060-T15	8	10	60	20	1.5°
2080-060-T20	8	10	60	20	2°
2080-060-T25	8	10	60	20	2.5°
2080-060-T30	8	12	60	20	3°
2100-070-T05	10	12	70	25	0.5°
2100-070-T10	10	12	70	25	1°
2100-070-T15	10	12	70	25	1.5°
2100-070-T20	10	12	70	25	2°
2100-070-T25	10	14	70	25	2.5°
2100-070-T30	10	14	70	25	3°
2110-070-T05	11	12	70	25	0.5°
2110-070-T10	11	12	70	25	1°
2110-070-T15	11	14	70	25	1.5°
2110-070-T20	11	14	70	25	2°
2110-070-T25	11	14	70	25	2.5°
2110-070-T30	11	14	70	25	3°
2120-075-T05	12	14	75	30	0.5°
2120-075-T10	12	14	75	30	1°
2120-075-T15	12	14	75	30	1.5°
2120-075-T20	12	16	75	30	2°
2120-075-T25	12	16	75	30	2.5°