


# FE2000-T (Коническая форма)



ØD	Предельные отклонения D
Ø1.0 ~ Ø8.0	0 ~ -0.020
Ø8.5 ~ Ø11.5	0 ~ -0.025
Ø12.0 ~ Ø20.0	0 ~ -0.030

(мм)

Обозначение	ØD	Ød	ℓ	L	θ°
<b>FE</b>					
<b>2</b> 2030-045-T05	3	6	10	45	0.5°
2030-045-T10	3	6	10	45	1°
2030-045-T15	3	6	10	45	1.5°
2030-045-T20	3	6	10	45	2°
2030-045-T25	3	6	10	45	2.5°
2030-045-T30	3	6	10	45	3°
2040-045-T05	4	6	12	45	0.5°
2040-045-T10	4	6	12	45	1°
2040-045-T15	4	6	12	45	1.5°
2040-045-T20	4	6	12	45	2°
2040-045-T25	4	6	12	45	2.5°
2040-045-T30	4	6	12	45	3°
2050-050-T05	5	6	15	50	0.5°
2050-050-T10	5	6	15	50	1°
2050-050-T15	5	6	15	50	1.5°
2050-050-T20	5	8	15	50	2°
2050-050-T25	5	8	15	50	2.5°
2050-050-T30	5	8	15	50	3°
2060-050-T05	6	8	15	50	0.5°
2060-050-T10	6	8	15	50	1°
2060-050-T15	6	8	15	50	1.5°
2060-050-T20	6	8	15	50	2°
2060-050-T25	6	8	15	50	2.5°
2060-050-T30	6	8	15	50	3°
2080-060-T05	8	10	20	60	0.5°
2080-060-T10	8	10	20	60	1°
2080-060-T15	8	10	20	60	1.5°
2080-060-T20	8	10	20	60	2°
2080-060-T25	8	10	20	60	2.5°
2080-060-T30	8	12	20	60	3°
2100-070-T05	10	12	25	70	0.5°
2100-070-T10	10	12	25	70	1°
2100-070-T15	10	12	25	70	1.5°
2100-070-T20	10	12	25	70	2°
2100-070-T25	10	14	25	70	2.5°
2100-070-T30	10	14	25	70	3°

