


I Патроны для зажима цилиндрических хвостовиков

HSK-SLA

DIN69893-1, ISO 12164-1 : 2001



Отверстие для подвода СОЖ (по запросу)

(мм)

Обозначение	ØD	ØC	L	L1	H	H1	M	G	
HSK 40A-SLA 6 -70	6	25	70	57	37	15	M6	M5	0.3
SLA 8 -70	8	28	70	57	37	15	M8	M6	0.3
SLA10 -75	10	35	75	62	43	17	M10	M8	0.3
SLA12 -80	12	42	80	67	49	20	M12	M8	0.4
SLA14 -85	14	44	85	72	49	20	M12	M8	0.6
SLA16 -85	16	48	85	72	55	22	M14	M8	0.6
HSK 50A-SLA 6 -80	6	25	80	54	37	15	M6	M5	0.8
SLA 8 -80	8	28	80	54	37	15	M8	M6	0.8
SLA10 -85	10	35	85	59	43	17	M10	M8	0.9
SLA12 -90	12	42	90	64	49	20	M12	M10	1.2
SLA14 -90	14	44	90	64	49	20	M12	M12	1.3
SLA16 -95	16	48	95	69	55	22	M14	M12	1.4
SLA18 -95	18	50	95	69	55	22	M14	M12	1.5
SLA20-100	20	52	100	74	68	25	M16	M12	1.6
HSK 63A-SLA 6 -80	6	25	80	54	37	15	M6	M5	1.0
SLA 8 -80	8	28	80	54	37	15	M8	M6	1.1
SLA10 -85	10	35	85	59	43	17	M10	M8	1.1
SLA12 -90	12	42	90	64	49	20	M12	M10	1.7
SLA14 -90	14	44	90	64	49	20	M12	M12	1.7
SLA16 -95	16	48	95	69	55	22	M14	M12	1.7
SLA18 -95	18	50	95	69	55	22	M14	M12	1.9
SLA20-100	20	52	100	75	68	25	M16	M12	2.0
SLA25-105	25	65	105	79	68	25	M18	M12	2.7
SLA32-105	32	72	105	79	72	30	M20	M12	2.9
HSK100A-SLA 6 -90	6	25	90	61	37	15	M6	M5	3.1
SLA 8 -90	8	28	90	61	37	15	M8	M6	3.3
SLA10 -90	10	35	90	61	43	17	M10	M8	3.5
SLA12 -95	12	42	95	66	49	20	M12	M10	3.5
SLA14 -95	14	44	95	66	49	20	M12	M12	3.6
SLA16-100	16	48	100	71	55	22	M14	M12	3.8
SLA18-100	18	50	100	71	55	22	M14	M12	3.8
SLA20-105	20	52	105	76	68	25	M16	M12	3.9
SLA25-110	25	65	110	81	68	25	M18	M12	4.0
SLA32-125	32	72	125	96	72	30	M20	M12	4.3
SLA40-135	40	80	135	106	78	32	M20	M12	4.4
SLA42-135	42	80	135	106	78	32	M20	M12	4.7

Возможность заказа балансированных патронов.

• Комплектующие смотреть на стр. 141,

