

Оправки для крепления торцевых фрез

BT-FMB MAS403-BT

Обозначение	Диаметр фрезы, мм	ØD	L	ØC	H	W	K	G	ØC1	H1	 kg	Исполнение №	(мм)
BT40 - FMB25.4 - 60	90	80	25.4	90	80	26	9.5	5	M12	33	10	4.8	4
	FMB38.1 - 60	100/125	38.1	60	85	26	15.9	9	M20	50	14	3.5	4
	FMB27 - 60	80	27	60	80	26	12	6	M12	33	10	3.6	4
		80	27	90	80	26	12	6	M12	33	10	4.8	4
	FMB40 - 60	100/125	40	60	85	26	16	8.5	M20	50	14	3.5	4
		80	25.4	45	80	26	9.5	5	M12	33	10	4.0	1
BT50 - FMB25.4 - 45	90	80	25.4	90	80	26	9.5	5	M12	33	10	5.8	1
	150	80	25.4	150	80	26	9.5	5	M12	33	10	8.2	2
	FMB38.1 - 45	100/125	38.1	45	85	26	15.9	9	M20	50	14	4.6	1
		100/125	38.1	75	85	26	15.9	9	M20	50	14	6.0	1
		100/125	38.1	105	85	26	15.9	9	M20	50	14	8.7	2
	FMB38.1F - 75	160	38.1	75	110	26	15.9	9	M20	50	14	6.6	5
	FMB27 - 45	80	27	45	80	26	12	6	M12	33	10	4.0	1
		80	27	90	80	26	12	6	M12	33	10	5.8	1
		80	27	150	80	26	12	6	M12	33	10	8.2	2
	FMB40 - 45	100/125	40	45	85	26	16	8.5	M20	50	14	4.6	1
		100/125	40	75	85	26	16	8.5	M20	50	14	6.0	1
		100/125	40	105	85	26	16	8.5	M20	50	14	8.7	2
	FMB40F - 75	160	40	75	110	26	16	8.5	M20	50	14	6.6	5
	FMB60 - 75	200	60	75	140	25	25.4	12.5	-	-	-	7.9	3

Комплектующие

Оправка	Комплектующие				
	Входящие в базовую комплектацию				Не входящие в базовую комплектацию
	Шпонка	Винт крепежный	Винт фланца	Винт фланца	Ключ
Серия					
FMB 25.4	K9.5	MBA - M12	BX0412	BX1225	LW-10
FMB 38.1	K15.87(F)	MBA - M20	BX0616	-	LW-17
FMB 38.1F	K15.87(F)	MBA - M20	BX0616	BX1230	LW-17
FMB 27	K12.0	MBA - M16	BX0516	BX1235	LW-14
FMB 40	K15.87(F)	MBA - M20	BX0616	-	LW-17
FMB 40F	K15.87(F)	MBA - M20	BX0616	BX1235	LW-17
FMB 60	K25.4(H)	-	BX1020	BX1645	-

