

HRMDC(M)16 *New*




Рис. 1




Рис. 2




Рис. 3




Рис. 4



AA
14°
• AR : -7°
• RR : -12°~4°

Обозначение	ØD	ØD2	Ød	Ød1	Ød2	Ød3	a	b	E	F	ap	kg	Крепежный винт	Рис.	
HRMDC(M) 16080HR-4	4	80	65	25.4(27)	14	20	-	9.5(12.4)	6(7)	25(23)	50	2.5	0.99	SB1230	1
16080HR-5	5	80	65	25.4(27)	14	20	-	9.5(12.4)	6(7)	25(23)	50	2.5	0.91		
16100HR-5	5	100	85	31.75(32)	18	26	-	12.7(14.4)	8	33(25)	63(50)	2.5	1.68	SB1630	1
16100HR-6	6	100	85	31.75(32)	18	26	-	12.7(14.4)	8	33(25)	63(50)	2.5	1.64		
16125HR-6	6	125	100	38.1(40)	22	32	52	15.9(16.4)	10(9)	36(29)	63	2.5	3.23	SB2040	1
16125HR-7	7	125	100	38.1(40)	22	32	52	15.9(16.4)	10(9)	36(29)	63	2.5	3.24		
16160R-7	7	160	107	50.8(40)	-	90	-	19(16.4)	11(9)	38(32)	63	2.5	3.73	MBA-M24	2
16160R-8	8	160	107	50.8(40)	-	90	-	19(16.4)	11(9)	38(32)	63	2.5	3.77		
16200R-8	8	200	145	47.625(60)	-	132	-	25.4(25.7)	14	38	63	2.5	6.48	-	3
16200R-10	10	200	145	47.625(60)	-	132	-	25.4(25.7)	14	38	63	2.5	6.61		
16250R-10	10	250	190	47.625(60)	-	190	-	25.4(25.7)	14	38	63	2.5	11.01	-	3
16250R-12	12	250	190	47.625(60)	-	190	-	25.4(25.7)	14	38	63	2.5	11.04		
16315R-12	12	315	250	47.625(60)	-	238	-	25.4(25.7)	14	38	63	2.5	18.34	-	4
16315R-14	14	315	250	47.625(60)	-	238	-	25.4(25.7)	14	38	63	2.5	18.35		

Применяемые СМП

WNMX-MM





Обозначение	Тв. сплав с покрытием							Кермет			Тв. сплав				Стр.			
	NCM325	NCM335	NC5330	PC3500	PC5300	PC5400	PC3545	PC9630	PC6510	PD2000	CN2000	CN20	CN30	H01		G10	ST30A	ST20
WNMX160720ZNN-MM					●	●												E23

Применяемые оправки


Обозначение	HRMDC	HRMDCM
HRMDC(M) 16080HR-4	BT□□-FMA25.4-□□	BT□□-FMC27-□□
16080HR-5		
16100HR-5	BT□□-FMA31.75-□□	BT□□-FMC32-□□
16100HR-6		
16125HR-6	BT□□-FMA38.1-□□	BT□□-FMB40-□□
16125HR-7		BT□□-FMC40-□□
16160R-7	BT□□-FMA50.8-□□	
16160R-8		
16200R-8		
16200R-10		
16250R-10	BT□□-FMA47.625-□□	BT□□-FMB60-□□
16250R-12		
16315R-12		
16315R-14		

Крепежный винт фрезы



Обозначение	Геометрические размеры, мм							Рис.
	M	a	b	b1	C	L	pitch	
SB1025	M10	16	10	-	-	25	1.5	1
SB1230	M12	18	12	-	-	30	1.75	1
SB1630	M16	24	16	-	-	30	2.0	1
SB2040	M20	30	20	-	-	40	2.5	1
MBA-M20	M20	50	14	20	27	30	2.5	2
MBA-M24	M24	65	14	24	37	36	3.0	2

Комплектующие



FTGA0513-P

TW20-100